




Architecture

8086 Microprocessor Architecture



جامعة
المنارة
MANARA UNIVERSITY



Execution Unit (EU)


EU executes instructions that have already been fetched by the BIU.

BIU and EU functions separately.

Bus Interface Unit (BIU)

BIU fetches instructions, reads data from memory and I/O ports, writes data to memory and I/O ports.

8086 Microprocessor Architecture



Bus Interface Unit (BIU)

Dedicated Adder to generate 20 bit address

Four 16-bit segment registers



**Code Segment (CS)
Data Segment (DS)
Stack Segment (SS)
Extra Segment (ES)**



جامعة
المنارة

Bus Interface Unit (BIU)

Segment Registers



- 8086's 1-megabyte memory is divided into segments of up to 64K bytes each.

- The 8086 can directly address four segments (256 K bytes within the 1 M byte of memory) at a particular time.


- Programs obtain access to code and data in the segments by changing the segment register content to point to the desired segments.



Segment Registers

Code Segment Register

- 16-bit
- CS contains the base or start of the current code segment; IP contains the distance or offset from this address to the next instruction byte to be fetched.
- BIU computes the 20-bit physical address by logically shifting the contents of CS 4-bits to the left and then adding the 16-bit contents of IP.
- That is, all instructions of a program are relative to the contents of the CS register multiplied by 16 and then offset is added provided by the IP.









Segment Registers

Data Segment Register

- 16-bit
- Points to the current data segment; operands for most instructions are fetched from this segment.
- The 16-bit contents of the Source Index (SI) or Destination Index (DI) or a 16-bit displacement are used as offset for computing the 20-bit physical address.



EU




BIU



Segment Registers

Stack Segment Register

- 16-bit
- Points to the current stack.
- The 20-bit physical stack address is calculated from the Stack Segment (SS) and the Stack Pointer (SP) for stack instructions such as **PUSH** and **POP**.
- In based addressing mode, the 20-bit physical stack address is calculated from the **Stack segment (SS)** and the Base Pointer (BP).









Segment Registers

Extra Segment Register

- 16-bit
- Points to the extra segment in which data (in excess of 64K pointed to by the DS) is stored.
- String instructions use the ES and DI to determine the 20-bit physical address for the destination.



EU





BIU




Segment Registers

Instruction Pointer

- 16-bit
- Always points to the next instruction to be executed within the currently executing code segment.
- So, this register contains the 16-bit offset address pointing to the next instruction code within the 64Kb of the code segment area.
- Its content is automatically incremented as the execution of the next instruction takes place.




EU



BIU

Bus Interface Unit (BIU)



Instruction queue

- A group of First-In-First-Out (FIFO) in which up to 6 bytes of instruction code are pre fetched from the memory ahead of time.
- This is done in order to speed up the execution by overlapping instruction fetch with execution.
- This mechanism is known as pipelining.



Architecture

EU decodes and executes instructions.

A decoder in the EU control system translates instructions.


16-bit ALU for performing arithmetic and logic operation

Four general purpose registers (AX, BX, CX, DX);

Pointer registers (Stack Pointer, Base Pointer);

and

Index registers (Source Index, Destination Index) each of 16-bits



Some of the 16 bit registers can be used as two 8 bit registers as :

AX can be used as AH and AL

BX can be used as BH and BL



CX can be used as CH and CL

DX can be used as DH and DL



EU Registers

Accumulator Register (AX)

- Consists of two 8-bit registers AL and AH, which can be combined together and used as a 16-bit register AX.
- AL in this case contains the low order byte of the word, and AH contains the high-order byte.
- The I/O instructions use the AX or AL for inputting / outputting 16 or 8 bit data to or from an I/O port.
- Multiplication and Division instructions also use the AX or AL.



EU






BIU




EU Registers

Base Register (BX)

- Consists of two 8-bit registers BL and BH, which can be combined together and used as a 16-bit register BX.
- BL in this case contains the low-order byte of the word, and BH contains the high-order byte.
- This is the only general purpose register whose contents can be used for addressing the 8086 memory.
- All memory references utilizing this register content for addressing use DS as the default segment register.



EU






BIU




EU Registers

Counter Register (CX)

- Consists of two 8-bit registers CL and CH, which can be combined together and used as a 16-bit register CX.
- When combined, CL register contains the low order byte of the word, and CH contains the high-order byte.
- Instructions such as **SHIFT**, **ROTATE** and **LOOP** use the contents of CX as a counter.



EU



BIU

Example:

The instruction **LOOP START** automatically decrements CX by 1 without affecting flags and will check if [CX] = 0.


If it is zero, 8086 executes the next instruction; otherwise the 8086 branches to the label **START**.



EU Registers

Data Register (DX)

- Consists of two 8-bit registers DL and DH, which can be combined together and used as a 16-bit register DX.
- When combined, DL register contains the low order byte of the word, and DH contains the high-order byte.
- Used to hold the high 16-bit result (data) in 16 X 16 multiplication or the high 16-bit dividend (data) before a $32 \div 16$ division and the 16-bit remainder after division.






Architecture

EU Registers

Stack Pointer (SP) and Base Pointer (BP)

- SP and BP are used to access data in the stack segment.
- SP is used as an offset from the current SS during execution of instructions that involve the stack segment in the external memory.
- SP contents are automatically updated (incremented/decremented) due to execution of a POP or PUSH instruction.
- BP contains an offset address in the current SS, which is used by instructions utilizing the based addressing mode.






Architecture

EU Registers

Source Index (SI) and Destination Index (DI)

- Used in indexed addressing.
- Instructions that process data strings use the SI and DI registers together with DS and ES respectively in order to distinguish between the source and destination addresses.






Architecture

EU Registers

Source Index (SI) and Destination Index (DI)


- Used in indexed addressing.
- Instructions that process data strings use the SI and DI registers together with DS and ES respectively in order to distinguish between the source and destination addresses.



Flag Register





Execution Unit (EU)





8086 registers
categorized
into 4 groups



Sl.No.	Type	Register width	Name of register
1	General purpose register	16 bit	AX, BX, CX, DX
		8 bit	AL, AH, BL, BH, CL, CH, DL, DH
2	Pointer register	16 bit	SP, BP
3	Index register	16 bit	SI, DI
4	Instruction Pointer	16 bit	IP
5	Segment register	16 bit	CS, DS, SS, ES
6	Flag (PSW)	16 bit	Flag register