

Appendix C

Average Filter :

```
A = im2double( imread('cameraman.tif') );
[r, c] = size(A);
B = zeros(r, c);

filter = (1/9)*[1, 1, 1; 1, 1, 1; 1, 1, 1];
filterSize = size(filter, 1);

start = floor(filterSize/2)+1;
stop_r = r - floor(filterSize/2);
stop_c = c - floor(filterSize/2);

for i = start:stop_r
    for j = start:stop_c
        B(i, j) = sum( sum( A(i-1:i+1, j-1:j+1) .*
filter ) );
    end
end

figure,
subplot(1, 2, 1), imshow(A, []), title('Before
filtering');

subplot(1, 2, 2), imshow(B, []),
title( strcat('After filtering using filter of the size =
', num2str(filterSize)) );
```

Before filtering



After filtering using filter of the size =3



Weighted mean filter :

```
A = im2double( imread('cameraman.tif') );
[r, c] = size(A);
B = zeros(r, c);

filter = (1/16)*[1, 2, 1; 2, 4, 2; 1, 2, 1];
filterSize = size(filter, 1);

start = floor(filterSize/2)+1;
stop_r = r - floor(filterSize/2);
stop_c = c - floor(filterSize/2);

for i = start:stop_r
    for j = start:stop_c
        B(i, j) = sum( sum( A(i-1:i+1, j-1:j+1).*
filter) ) );
    end
end

figure,
subplot(1, 2, 1), imshow(A, []), title('Before
filtering');

subplot(1, 2, 2), imshow(B, []),
title( strcat('After filtering using filter of the size =
', num2str(filterSize)) );
```



Gaussian filter :

```
InputImage = im2double( imread('cameraman.tif') );

Mean = 0.02;
Variance = 0.025;
NoisyImage =
imnoise(InputImage, 'gaussian', Mean, Variance);
```

```

filterSize = 7;
filterSigma = 3;
GaussianFilter = fspecial('gaussian', filterSize,
filterSigma);

FilteredImage1 = imfilter(NoisyImage, GaussianFilter,
'conv' , 'replicate');

FilteredImage2 = imgaussfilt(NoisyImage, filterSigma/1.5);

subplot(2,2,1)
imshow(InputImage, []);
title ('Input image ');

subplot(2,2,2)
imshow(NoisyImage, []);
title ('Noisy image ');

subplot(2,2,3)
imshow(FilteredImage1, []);
title ('Filtered image using imfilter ');

subplot(2,2,4)
imshow(FilteredImage2, []);
title ('Filtered image using imgaussfilt ');

```

Input image



Noisy image



Filtered image using imfilter



Filtered image using imgaussfilt




Non-linear filters :

```
A = im2double( imread('cameraman.tif') );
B = imnoise(A, 'salt & pepper', 0.02);
[r, c] = size(B);

C1 = zeros(r, c);
C2 = C1;
C3 = C2;

for i=2:r-1
    for j=2:c-1
        mask = B(i-1:i+1, j-1:j+1);
        sorted_mask = sort(mask)
        min_ = sorted_mask (0);
        max_ = sorted_mask (9);
        median_ = sorted_mask (5);
        C1(i, j) = min_;
        C2(i, j) = max_;
        C3(i, j) = median_;
    end
end

figure,
subplot(2, 2, 1), imshow(B);
subplot(2, 2, 2), imshow(C1), title('Min');
subplot(2, 2, 3), imshow(C2), title('Max');
subplot(2, 2, 4), imshow(C3), title('Median');
```



Prewit edge detector :

```
I = imread('squares.jpg');
I = rgb2gray(I);
I = im2double(I);
[r, c] = size(I);

mask_x = [1 1 1; ...
          0 0 0; ...
          -1 -1 -1];

mask_y = mask_x';

Ix = zeros(r, c);
Iy = Ix;
Ixy = Iy;


Ix = imfilter(I, mask_x, 'conv', 'same');
Iy = imfilter(I, mask_y, 'conv', 'same');
Ixy = sqrt( Ix.^2 + Iy.^2 );
phi = atan2(Iy, Ix);

figure, subplot(2, 2, 1),
imshow(Ix);
title('Ix');

subplot(2, 2, 2),
imshow(Iy);
title('Iy');

subplot(2, 2, 3),
imshow(Ixy);
title('Ixy');

subplot(2, 2, 4),
imshow(phi, []);
title('Phi');
```



Sobel edge detector :

```

I = imread('squares.jpg');
I = rgb2gray(I);
I = im2double(I);
[r, c] = size(I);

mask_x = [1 2 1; ...
          0 0 0; ...
          -1 -2 -1];

mask_y = mask_x';

Ix = zeros(r, c);
Iy = Ix;
Ixy = Iy;

Ix = imfilter(I, mask_x, 'conv', 'same');
Iy = imfilter(I, mask_y, 'conv', 'same');
Ixy = sqrt( Ix.^2 + Iy.^2 );
phi = atan2(Iy, Ix);





figure, subplot(2, 2, 1),
imshow(Ix);
title('Ix');

subplot(2, 2, 2),
imshow(Iy);
title('Iy');

subplot(2, 2, 3),
imshow(Ixy);

```

```
title('Ixy');  
  
subplot(2, 2, 4),  
imshow(phi, []);  
title('Phi');
```



Prepared by :
Ali Ali

2025 – 2026
1st term